

## LYMAN : POUSSOIR DE BALLE POUR PRESSE A CALIBRER

CALIBRE	DIAMETRE	REFERENCE A PRECISER	CALIBRE	DIAMETRE	REFERENCE A PRECISER
.30	.465	<b>2786742</b>	.30M1/7,62x39mm	.359	<b>2786772</b>
.32	.226	<b>2786703</b>	.30M1/7,62x39mm	.467	<b>2786743</b>
9mm	.311	<b>2786710</b>	.30	.644	<b>2786758</b>
9mm	.402	<b>2786723</b>	.30	.465	<b>2786742</b>
9mm	.637	<b>2786749</b>	.30	.8	<b>2786690</b>
.38/.357	.495	<b>2786769</b>	.30	.413	<b>2786725</b>
.38/.357	.429	<b>2786731</b>	.30	.359	<b>2786772</b>
.38/.357	.311	<b>2786710</b>	.30	.467	<b>2786743</b>
.38/.357	.430	<b>2786732</b>	.30	.284	<b>2786707</b>
40 S&W/10mm	.43	<b>2786691</b>	.32/20	.8	<b>2786690</b>
.38/40	.43	<b>2786691</b>	.314 dia.	.467	<b>2786690</b>
.44/40	.649	<b>2786778</b>	32/40	.8	<b>2786690</b>
.44/40	.43	<b>2786691</b>	8mm	.470	<b>2786745</b>
.44	.421	<b>2786729</b>	35	.311	<b>2786710</b>
.44	.649	<b>2786778</b>	.375/.38-55	.449	<b>2786736</b>
.44	.251	<b>2786704</b>	.378/.38-55	.663	<b>2786779</b>
.45 auto	.460	<b>2786740</b>	.40 Cal. / .406 dia.	.43	<b>2786691</b>
.45 auto	.374	<b>2786719</b>	.40	.678	<b>2786785</b>
.45 Colt	.190	<b>2786700</b>	.40 Cal. / .410 dia.	.449	<b>2786736</b>
.45 Colt	.649	<b>2786778</b>	.40 Cal. / .410 dia.	.658	<b>2786755</b>
.45 Colt	.424	<b>2786730</b>	405	.132	<b>2786695</b>
.45	.649	<b>2786778</b>	43 Span.	.251	<b>2786704</b>
500 S&W	.649	<b>2786778</b>	43 Mauser	.251	<b>2786704</b>
38 spec/9mm	.637	<b>2786749</b>	45 H.P.	.191	<b>2786701</b>
.45	.374	<b>2786719</b>	45 H.P.	.374	<b>2786719</b>
.22	.438	<b>2786733</b>	45 H.P.	.658	<b>2786755</b>
.22	.415	<b>2786726</b>	45 H.P.	.677	<b>2786781</b>
.22	.646	<b>2786759</b>	45 H.P.	.132	<b>2786695</b>
.25	.420	<b>2786728</b>	.50	.141	<b>2786696</b>
6,5mm	.463	<b>2786741</b>	.50	.191	<b>2786701</b>
6,5mm	.641	<b>2786753</b>	.50	.649	<b>2786778</b>
7mm	.641	<b>2786753</b>			