



35 Remington (Rifle)

.358"	35
Weight (grains)	SPFN Hot-Cor®
Ballistic Coefficient	220
Sectional Density	0.286
COAL Tested	0.245
Speer Part No.	2.470"
	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	38.0	1920	41.2 C	2031
Alliant AR-Comp	Federal	Federal 210	30.2	1780	33.0	1925
Accurate 2015	Winchester	CCI 200	29.0	1666	33.0	1915
Hodgdon CFE 223	Federal	Federal 210	32.9	1797	35.3	1901
IMR 4064	Winchester	CCI 200	32.0	1641	36.0	1851
Hodgdon H414	Winchester	CCI 250	36.0	1656	40.0	1841
Winchester 748	Winchester	CCI 250	31.0	1675	35.0	1840
IMR 8208 XBR	Federal	Federal 210	29.0	1647	32.1	1840
Alliant Reloder 15	Federal	Federal 210	31.4	1643	34.9	1824
Alliant Power Pro Varmint	Federal	Federal 210	29.7	1650	32.6	1822
Vihtavuori N133	Winchester	CCI 200	27.0	1591	31.0	1816
Hodgdon BL-C(2)	Winchester	CCI 250	31.0	1552	35.0	1802
IMR 4895	Winchester	CCI 200	31.5	1640	35.5	1797
Hodgdon H335	Winchester	CCI 250	28.0	1467	32.0	1792
IMR 3031	Winchester	CCI 200	29.5	1525	33.5	1788
IMR 4320	Winchester	CCI 200	29.0	1494	33.0	1694
Alliant Reloder 7	Winchester	CCI 200	20.5	1149	24.5	1530

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load



35 Whelen

.358"	35
	SPFN Hot-Cor®
Weight (grains)	220
Ballistic Coefficient	0.286
Sectional Density	0.245
COAL Tested	3.060"
Speer Part No.	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro Varmint	Federal	Federal 210	57.8	2615	63.8 C	2826
Hodgdon CFE 223	Federal	Federal 210	61.0	2536	67.0 C	2788
Alliant Power Pro 2000-MR	Federal	Federal 210	62.2	2546	68.5 C	2786
Alliant AR-Comp	Federal	Federal 210	55.1	2557	61.0 C	2777
IMR 8208 XBR	Federal	Federal 210	52.8	2522	58.6	2741
Alliant Reloder 15	Remington	CCI 200	56.0	2445	60.0 C	2628
Winchester 748	Remington	CCI 250	59.0	2542	63.0 C	2588
Hodgdon H335	Remington	CCI 250	52.0	2312	56.0	2586
Accurate 2460	Remington	CCI 250	50.0	2390	54.0	2520
Vihtavuori N140	Remington	CCI 200	54.0	2330	58.0 C	2505
IMR 4451	Federal	Federal 210	57.1	2258	63.0 C	2504
IMR 3031	Remington	CCI 200	51.0	2294	55.0 C	2503
Hodgdon BL-C(2)	Remington	CCI 250	53.0	2371	57.0	2481
IMR 4064	Remington	CCI 200	52.0	2260	56.0 C	2468
Hodgdon H380	Remington	CCI 250	57.0	2300	61.0 C	2445
Accurate 2015	Remington	CCI 200	45.0	2252	49.0	2438
IMR 4895	Remington	CCI 200	49.0	2332	53.0	2400
Hodgdon H322	Remington	CCI 200	45.0	2236	49.0	2397
IMR 4320	Remington	CCI 200	50.0	2113	54.0	2298

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load



356 Winchester

.358"

35
SPFN Hot-Cor®

Weight (grains)	220
Ballistic Coefficient	0.286
Sectional Density	0.245
COAL Tested	2.550"
Speer Part No.	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Winchester	CCI 200	39.0	2173	44.0	2389
Accurate 2015	Winchester	CCI 200	38.0	2141	42.0 C	2386
Alliant Power Pro Varmint	Winchester	CCI 200	42.5	2234	46.4	2381
Winchester 748	Winchester	CCI 250	45.5	2172	49.5	2369
Vihtavuori N135	Winchester	CCI 200	41.0	2156	45.0 C	2345
IMR 4064	Winchester	CCI 200	42.0	2046	46.0	2340
IMR 4166	Winchester	CCI 200	40.5	2193	43.8	2339
Hodgdon H322	Winchester	CCI 200	39.0	2144	43.0	2323
IMR 4320	Winchester	CCI 200	42.0	2125	46.0	2310
Hodgdon H335	Winchester	CCI 250	39.0	2063	43.0	2294
IMR 4895	Winchester	CCI 200	42.0	2006	46.0	2278
Hodgdon BL-C(2)	Winchester	CCI 250	42.0	2054	46.0 C	2277
Hodgdon H380	Winchester	CCI 250	46.0	1992	50.0 C	2143
Alliant Reloder 7	Winchester	CCI 200	31.0	1877	35.0	2116

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load



358 Winchester

.358"	35
	SPFN Hot-Cor®
Weight (grains)	220
Ballistic Coefficient	0.286
Sectional Density	0.245
COAL Tested	2.565"
Speer Part No.	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	Winchester	CCI 250	48.0	2348	52.0	2506
Vihtavuori N135	Winchester	CCI 200	44.0	2309	48.0 C	2476
IMR 3031	Winchester	CCI 200	43.0	2232	47.0	2474
Alliant Power Pro Varmint	Hornady	CCI 200	47.0	2342	50.6	2473
Accurate 2520	Winchester	CCI 250	44.0	2287	48.0 C	2455
Hodgdon H322	Winchester	CCI 200	41.0	2070	45.0	2434
Hodgdon H335	Winchester	CCI 250	43.5	2244	47.5	2428
IMR 4064	Winchester	CCI 200	44.0	2280	48.0	2427
IMR 4320	Winchester	CCI 200	43.5	2213	47.5	2393
IMR 8208	Hornady	CCI 200	43.0	2262	46.3	2392
Accurate 2015	Winchester	CCI 200	39.0	2202	43.0	2390
Hodgdon BLC-(2)	Winchester	CCI 250	46.0	2207	50.0 C	2388
IMR 4166	Hornady	CCI 200	42.5	2147	45.8	2285
Hodgdon H380	Winchester	CCI 250	46.0	2002	50.0 C	2231
Alliant Reloder 7	Winchester	CCI 200	34.0	2089	38.0	2209

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load



350 Remington Magnum

.358"	35
Weight (grains)	SPFN Hot-Cor®
Ballistic Coefficient	220
Sectional Density	0.286
COAL Tested	0.245
Speer Part No.	2.740"
	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon BL-C(2)	Remington	CCI 250	56.0	2522	60.0	2708
Winchester 748	Remington	CCI 250	58.0	2515	62.0	2696
IMR 4895	Remington	CCI 200	56.0	2552	60.0	2686
IMR 3031	Remington	CCI 200	55.0	2475	59.0	2673
IMR 4320	Remington	CCI 200	56.0	2471	60.0 C	2660
Hodgdon H322	Remington	CCI 200	51.0	2452	55.0 C	2591
Hodgdon H380	Remington	CCI 250	58.0	2430	62.0 C	2522
Winchester 760	Remington	CCI 250	61.0	2320	65.0 C	2496
Alliant Reloder 7	Remington	CCI 200	45.5	2258	49.5	2450

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load