

# Rifle Reloading data

## Cartridge

Cartridge	7,62 x 39
Test barrel	415 mm (16"), 1 in 9½" twist
Primers	Large Rifle
Cases	Lapua, trim-to length 38,50 mm (1.516")



VIHTAVUORI

## Bullet specifications

Your search returned **24** different loads:

Bullet				Powder	Load			
g				mm			m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
3,7	Lapua	ALS	55,7	N110	1,56	1,78	925	997
6,5	Lapua	HP / OTCE	55,4	N110	1,22	1,41	685	772
6,5	Lapua	HP / OTCE	55,4	N120	1,65	1,80	688	769
7,1	H&N	RN HS	50,5	N110	0,90	1,00	498	527
7,1	H&N	RN HS	50,5	N120	1,20	1,25	509	548
7,1	Hornady	CX	59,5	N120	1,50	1,75	687	777
7,1	Hornady	CX	59,5	N130	1,70	1,80	696	729
8,0	Berry's	TMJ Spire Point	55,1	N120	1,25	1,32	549	587
8,0	Lapua	FMJ	55,7	N120	1,60	1,77	663	728
8,0	Nosler	Varmageddon	56,0	N110	1,05	1,17	601	651
8,0	Nosler	Varmageddon	56,0	N120	1,46	1,65	644	712
8,0	Nosler	Varmageddon	56,0	N130	1,65	1,80	670	725
8,1	Hornady	ECX	56,0	N110	1,00	1,11	567	607
8,1	Hornady	ECX	56,0	N120	1,45	1,66	627	710
8,1	Hornady	ECX	56,0	N130	1,60	1,80	634	700
8,1	Sierra	TMK	58,0	N110	1,05	1,19	607	656
8,1	Sierra	TMK	58,0	N120	1,50	1,64	657	719
8,1	Sierra	TMK	58,0	N130	1,64	1,80	660	712
9,7	Lapua	LockBase	56,0	N120	1,43	1,58	605	666
9,7	X-Treme Bullets	Flat Point	55,0	N110	0,90	1,00	465	535
9,7	X-Treme Bullets	Flat Point	55,0	N120	1,10	1,30	424	535
13,0	Lapua	B416 FMJBT	56,0	N110	0,87	0,97	435	481
13,0	Lapua	B416 FMJBT	56,0	N120	1,21	1,33	493	542
13,0	Lapua	B416 FMJBT	56,0	N130	1,30	1,45	499	553