

# Rifle Reloading data

## Cartridge

Cartridge	8 x 68 S
Test barrel	670 mm (26"), 1 in 11" twist
Primers	Large Rifle
Cases	RWS, trim-to length 67,50 mm (2.646")



VIHTAVUORI

## Bullet specifications

Your search returned **27** different loads:

Bullet				Powder	Load			
g				mm			m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
7,8	Lapua	OT, G573	86,4	N135	3,40	3,87	956	1053
7,8	Lapua	OT, G573	86,4	N140	3,91	4,28	990	1080
7,8	Lapua	OT, G573	86,4	N150	3,63	4,22	988	1091
9,7	Sierra	Pro Hunter Spitzer	86,4	N150	4,00	4,48	924	1021
9,7	Sierra	Pro Hunter Spitzer	86,4	N550	4,32	4,75	946	1044
9,7	Sierra	Pro Hunter Spitzer	86,4	N160	4,69	5,12	945	1031
10,4	Barnes	TTSX	86,4	N150	3,55	4,07	850	952
10,4	Barnes	TTSX	86,4	N550	3,79	4,28	876	989
10,4	Barnes	TTSX	86,4	N160	4,16	4,67	877	987
11,3	Brenneke	TAG	87,0	N550	3,85	4,27	851	942
11,3	Brenneke	TAG	87,0	N160	4,02	4,65	837	947
11,3	Brenneke	TAG	87,0	N560	4,40	4,97	853	957
11,7	Lapua	Naturalis N559	86,4	N150	3,52	4,00	819	907
11,7	Lapua	Naturalis N559	86,4	N550	3,83	4,22	847	935
11,7	Lapua	Naturalis N559	86,4	N160	4,14	4,62	840	937
11,7	Nosler	Expansion Tip	87,0	N150	3,35	3,92	790	885
11,7	Nosler	Expansion Tip	87,0	N550	3,79	4,21	825	921
11,7	Nosler	Expansion Tip	87,0	N160	3,82	4,62	803	923
13,0	Barnes	TSX	87,0	N160	3,60	4,21	735	854
13,0	Barnes	TSX	87,0	N560	4,15	4,65	783	888
13,0	Barnes	TSX	87,0	N565	4,43	5,00	796	879
13,0	Nosler	Accubond	87,0	N550	3,79	4,16	809	888
13,0	Nosler	Accubond	87,0	N160	4,13	4,56	810	890
13,0	Nosler	Accubond	87,0	N560	4,45	4,97	815	912
14,2	Brenneke	TOG	87,1	N160	3,58	4,11	708	805
14,2	Brenneke	TOG	87,1	N560	3,95	4,42	736	831

Bullet				Powder	Load			
g				mm			g	m/s
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
14,2	Brenneke	TOG	87,1	N565	4,18	4,85	749	848