

Rifle Reloading data

Cartridge

Cartridge	.30-30 Winchester
Test barrel	510 mm (20"), 1 in 12" twist
Primers	Large Rifle
Cases	Remington, trim-to length 51,60 mm (2.031")



Bullet specifications

Your search returned **16** different loads:

Bullet				Powder	Load			
g			mm		g	m/s		
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
6,8	Lapua	HP	64,5	N120	1,48	1,73	692	781
6,8	Lapua	HP	64,5	N130	1,70	1,95	710	800
6,8	Lapua	HP	64,5	N133	1,86	2,19	730	833
8,5	Speer	FSP	64,7	N120	1,41	1,67	617	705
8,5	Speer	FSP	64,7	N130	1,59	1,84	641	728
8,5	Speer	FSP	64,7	N133	1,71	1,97	653	741
8,5	Speer	FSP	64,7	N135	1,80	2,08	649	737
9,7	Speer	FSP	64,5	N120	1,23	1,46	519	593
9,7	Speer	FSP	64,5	N130	1,43	1,65	558	631
9,7	Speer	FSP	64,5	N133	1,48	1,72	560	636
9,7	Speer	FSP	64,5	N135	1,71	1,93	587	660
9,7	Speer	FSP	64,5	N140	1,85	2,06	596	672
11,0	Speer	FSP	64,5	N130	1,34	1,60	516	598
11,0	Speer	FSP	64,5	N133	1,42	1,67	511	589
11,0	Speer	FSP	64,5	N135	1,58	1,80	536	604
11,0	Speer	FSP	64,5	N140	1,66	1,89	533	610