

Rifle Reloading data

Cartridge

Cartridge	7 x 57R
Test barrel	550 mm (22"), 1 in 9½" twist
Primers	Large Rifle
Cases	RWS, trim-to length 56,80 mm (2.236")



VIHTAVUORI

Bullet specifications

Your search returned **26** different loads:

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
7,8	Sierra	Spitzer	76,5	N135	2,58	2,79	785	857
7,8	Sierra	Spitzer	76,5	N140	2,72	2,97	791	870
7,8	Sierra	Spitzer	76,5	N150	2,74	3,00	797	873
9,1	Nosler	Ballistic Tip	77,5	N140	2,47	2,74	707	777
9,1	Nosler	Ballistic Tip	77,5	N150	2,53	2,81	718	787
9,7	Barnes	TSX	76,5	N540	2,38	2,58	696	759
9,7	Barnes	TSX	76,5	N150	2,23	2,51	663	729
9,7	Barnes	TSX	76,5	N550	2,58	2,77	702	767
9,7	Brenneke	TOG	76,5	N540	2,33	2,67	700	772
9,7	Brenneke	TOG	76,5	N150	2,32	2,57	685	738
9,7	Brenneke	TOG	76,5	N550	2,67	2,86	718	779
9,7	Brenneke	TOG	76,5	N160	2,99	3,19	723	776
9,7	Lapua	Scenar-L	76,5	N540	2,40	2,58	727	780
9,7	Lapua	Scenar-L	76,5	N150	2,33	2,57	707	768
9,7	Lapua	Scenar-L	76,5	N550	2,50	2,70	725	782
9,7	Lapua	Scenar-L	76,5	N160	2,84	3,06	741	798
10,4	Lapua	Naturalis	75,0	N140	2,17	2,41	643	701
10,4	Lapua	Naturalis	75,0	N540	2,26	2,53	645	715
10,4	Lapua	Naturalis	75,0	N150	2,08	2,47	603	702
10,4	Sierra	SPBT	77,5	N150	2,39	2,66	662	731
10,4	Sierra	SPBT	77,5	N160	2,93	3,19	693	774
11,3	Barnes	TSX	76,5	N550	2,26	2,52	602	676
11,3	Barnes	TSX	76,5	N160	2,47	2,80	603	672
11,3	Barnes	TSX	76,5	N560	2,80	3,14	636	711
11,3	Speer	Mag-Tip	77,0	N160	2,63	2,95	629	701
11,3	Speer	Mag-Tip	77,0	N165	2,78	3,17	631	711

