

Rifle Reloading data

Cartridge

Cartridge	7 x 64
Test barrel	600 mm (23½"), 1 in 10" twist
Primers	Large Rifle
Cases	Norma, trim-to length 63,80 mm (2.512")



VIHTAVUORI

Bullet specifications

Your search returned **50** different loads:

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
7,8	Nosler	Ballistic Tip	82,0	N540	3,03	3,34	888	982
7,8	Nosler	Ballistic Tip	82,0	N150	2,94	3,24	863	946
7,8	Nosler	Ballistic Tip	82,0	N550	3,16	3,55	884	983
7,8	Nosler	Ballistic Tip	82,0	N160	3,52	3,70	892	930
9,1	Swift	A-Frame	81,4	N540	2,74	3,15	788	887
9,1	Swift	A-Frame	81,4	N150	2,66	3,10	766	856
9,1	Swift	A-Frame	81,4	N550	3,04	3,32	802	889
9,1	Swift	A-Frame	81,4	N160	3,31	3,60	797	889
9,1	Swift	A-Frame	81,4	N560	3,56	3,88	811	909
9,7	Barnes	TSX	83,8	N540	2,74	3,06	753	846
9,7	Barnes	TSX	83,8	N150	2,65	2,99	721	813
9,7	Barnes	TSX	83,8	N550	2,94	3,24	765	855
9,7	Barnes	TSX	83,8	N160	3,19	3,61	760	861
9,7	Barnes	TSX	83,8	N560	3,52	3,91	787	892
9,7	Lapua	Scenar-L	84,0	N540	2,71	3,03	779	866
9,7	Lapua	Scenar-L	84,0	N150	2,64	3,01	757	845
9,7	Lapua	Scenar-L	84,0	N550	2,92	3,16	787	867
9,7	Lapua	Scenar-L	84,0	N160	3,22	3,57	794	881
9,7	Lapua	Scenar-L	84,0	N560	3,33	3,65	796	884
9,7	Nosler	Partition	83,8	N540	2,68	3,14	774	871
9,7	Nosler	Partition	83,8	N150	2,66	3,09	758	843
9,7	Nosler	Partition	83,8	N550	3,04	3,33	795	871
9,7	Nosler	Partition	83,8	N160	3,30	3,59	790	874
9,7	Nosler	Partition	83,8	N560	3,43	3,76	800	888
10,1	Lapua	Naturalis N564	83,0	N150	2,60	2,96	736	816
10,1	Lapua	Naturalis N564	83,0	N550	2,81	3,16	750	840

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
10,1	Lapua	Naturalis N564	83,0	N160	3,19	3,52	764	837
10,1	Lapua	Naturalis N564	83,0	N560	3,33	3,71	747	866
10,4	Nosler	Accubond	84,0	N540	2,64	3,04	746	835
10,4	Nosler	Accubond	84,0	N150	2,56	2,99	731	810
10,4	Nosler	Accubond	84,0	N550	2,92	3,20	759	839
10,4	Nosler	Accubond	84,0	N160	3,27	3,60	767	854
11,3	Barnes	TSX	81,3	N540	2,44	2,95	655	765
11,3	Barnes	TSX	81,3	N550	2,78	3,24	675	784
11,3	Barnes	TSX	81,3	N160	3,04	3,47	676	781
11,3	Sierra	Game King	84,0	N540	2,57	2,98	718	803
11,3	Sierra	Game King	84,0	N550	2,84	3,09	733	805
11,3	Sierra	Game King	84,0	N160	3,12	3,41	737	812
11,3	Sierra	Game King	84,0	N165	3,40	3,75	752	823
11,3	Sierra	Game King	84,0	N560	3,31	3,70	750	837
11,5	Brenneke	TIG	82,3	N540	2,53	2,92	687	774
11,5	Brenneke	TIG	82,3	N550	2,81	3,11	701	783
11,5	Brenneke	TIG	82,3	N160	3,06	3,46	703	791
11,5	Brenneke	TIG	82,3	N165	3,43	3,80	724	815
11,5	Brenneke	TIG	82,3	N560	3,31	3,72	730	814
11,7	Lapua	Scenar-L	84,0	N540	2,57	2,86	702	781
11,7	Lapua	Scenar-L	84,0	N550	2,75	3,02	701	787
11,7	Lapua	Scenar-L	84,0	N160	3,04	3,40	716	799
11,7	Lapua	Scenar-L	84,0	N165	3,41	3,60	743	789
11,7	Lapua	Scenar-L	84,0	N560	3,20	3,66	701	821